



Technical Data

Solar Pump Inverter - GLP3KL

Revision no.

Page:

1

Receiver

From

Company name
Respons. Department
Person in charge
Phone number
Fax no
E-mail address

**Brand: Gol Pumps****Model: GLP3KL****Net Weight (lb): 32**

D.C. INPUT

PARAMETER	GLP3KL
D.C. Max Input Voltage	440 VDC
Recommended MPPT Voltage Range	150~400Vdc
D.C. Max. Input Current	21A
Max. MPPT Efficiency	99%
Number of String	2

A.C. OUTPUT

PARAMETER	GLP3KL
Max. Motor Output Power	3kW
Rated Output Voltage	220~240Vac, Three Phase
Output Frequency Range	0~50/60Hz
Rated Output Current	14 A

Other Parameters

Model	GLP3KL
Weight(lbs)	32
Dimension(L*W*H)	10.5 x 12 x 8 inch
Max. Efficiency	97%
Protection Class	I
Protection Level	IP65
Operating Temperature	-25°C~+60°C; above 60°C need derate operating
Cooling Way	Natural Cooling
Display	LCD
Communication	RS485/GPRS
Altitude	3000m;above 3000m need derate operating
Noise Emission	<50dB
Compliance	EN50178;IEC/EN62109-1;IEC 61800

Project

Project ID

Created by

Created on

Last update